

### **AMENDMENTS TO THE CLAIMS**

Please amend claims 1, 7, 15, and 23. Following is a complete listing of the claims pending in the application, as amended:

1. (Currently Amended) A laser, comprising:  
a laser source;  
a power source for causing the laser source to generate a laser beam, wherein the power source is configured to provide excitation energy for a lasing medium;  
a fan for generating an air flow;  
wherein the laser source and the power source each have an exterior surface;  
and  
wherein the laser source and the power source are arranged in an end-to-end series relation along a longitudinal axis such that the fan directs the air flow generally parallel with the longitudinal axis to pass first adjacent to the exterior surface of the laser source for the cooling thereof, and then to pass adjacent to the exterior surface of the power source for subsequent cooling thereof.
2. (Previously Presented) The laser of claim 1, wherein each of the exterior surfaces of said laser source and said power source includes:  
a substantially developed surface to facilitate transfer of heat to air, wherein the fan directs the air flow substantially adjacent to the developed surface of each of said laser source and said power source.
3. (Original) The laser of claim 2, wherein said developed surfaces are cooling fins.
4. (Original) The laser of claim 3, wherein said cooling fins on said laser source are profiled in a direction along the longitudinal axis of the laser.

5. (Original) The laser of claim 1, wherein said laser source and said power source have generally equal cross-sectional areas in a direction perpendicular to the longitudinal axis.

6. (Previously Presented) The laser of claim 1, further comprising:  
a shroud covering said laser source and said power source, wherein said shroud includes interior walls forming a single air channel configured to direct the air flow within the shroud in a single direction from the fan along the longitudinal axis to pass substantially adjacent to the exterior surfaces of said laser source and said power source.

7. (Currently Amended) A laser, comprising:  
a laser source having a first end, a second end spaced apart from a first end along a longitudinal axis, a laser resonator, a laser media, and electrodes for exciting the laser media;  
a power source at least proximate to one of the first or second ends of said laser source and configured to provide excitation energy to the electrodes and cause ~~adapted for causing the~~ laser source to generate a laser beam from the other one of the first or second ends, wherein the power source and the laser source are aligned along the longitudinal axis; and  
a cooling fan positioned adjacent to said power source and located in a generally straight line path with said laser source and said power source along the longitudinal axis, said cooling fan adapted for generating an air flow for cooling said laser source and said power source.

8. (Original) The laser of claim 7, wherein said cooling fan generates the air flow in a direction to cool said laser source before cooling said power source.

9. (Original) The laser of claim 7, wherein said cooling fan generates the air flow in a direction to cool said power source before cooling said laser source.

10. (Previously Presented) The laser of claim 7, wherein each of said laser source and said power source includes:

a substantially developed surface to facilitate a transfer of heat to air on a respective exterior surface, and

wherein said cooling fan directs the air flow substantially adjacent to the developed surface of each of said laser source and said power source.

11. (Original) The laser of claim 10, wherein said developed surfaces are cooling fins.

12. (Original) The laser of claim 11, wherein said cooling fins on said laser source are profiled in a direction along the longitudinal axis of the laser.

13. (Original) The laser of claim 7, wherein said laser source and said power source have generally equal cross-sectional areas in a direction perpendicular to the generally straight line path.

14. (Original) The laser of claim 7, further comprising:

a shroud for covering said laser source and said power source, with said shroud forming a single air channel for directing the air flow along the generally straight line path to pass substantially adjacent said laser source and said power source.

15. (Currently Amended) A laser, comprising:

a laser source;

a power source at least proximate to said laser source and ~~adapted for causing~~  
configured to provide excitation energy for a lasing medium of the laser  
source to generate a laser beam; and

a cooling fan at one end of the power source, the cooling fan being adapted for generating an air flow directed in a generally straight line path with said

laser source and said power source for cooling said laser source and said power source.

16. (Original) The laser of claim 15, wherein said cooling fan generates the air flow in a direction to cool said laser source before cooling said power source.

17. (Original) The laser of claim 15, wherein said cooling fan generates the air flow in a direction to cool said power source before cooling said laser source.

18. (Previously Presented) The laser of claim 15, wherein each of said laser source and said power source includes:

a substantially developed surface to facilitate transfer of heat to air on a respective exterior surface, and

wherein said cooling fan directs the air flow substantially adjacent to the developed surface of each of said laser source and said power source.

19. (Original) The laser of claim 18, wherein said developed surfaces are cooling fins.

20. (Original) The laser of claim 19, wherein said cooling fins on said laser source are profiled in a direction along the longitudinal axis of the laser.

21. (Original) The laser of claim 15, wherein said laser source and said power source have generally equal cross-sectional areas in a direction perpendicular to the generally straight line path.

22. (Original) The laser of claim 15, further comprising:

a shroud for covering said laser source and said power source, with said shroud forming a single air channel for directing the air flow along the generally straight line path to pass substantially adjacent said laser source and said power source.

23. (Currently Amended) A laser, comprising:
- a laser source having a first end, a second end spaced apart from a first end along a longitudinal axis, a laser resonator, a laser media, and electrodes for exciting the laser media;
  - a power source at least proximate to one of the first or second ends of the laser source and configured to provide excitation energy to the electrodes ~~adapted for causing and cause~~ the laser source to generate a laser beam, wherein the power source and the laser source are aligned along the longitudinal axis; and
  - a cooling fan positioned adjacent to the power source and in a generally straight line path with the laser source and the power source along the longitudinal axis, wherein the cooling fan is adapted for generating an air flow for cooling the laser source and the power source.